



Part Number: 377.0156.00

Optical Transceiver SFP MS850 ETH [-/1.25G] [DD/VCSEL/-/OP:-9,5/RP:-17/0,55km]

PRODUCT DESCRIPTION

377.0156.00

Optical Transceiver SFP MS850 ETH [-/1.25G] [DD/VCSEL/-/OP:-9,5/RP:-17/0,55km]

FEATURES

SFP Optical Transceiver for 1.25G bps, with a typical range of 0.55 km.

Compatibilities:

IEEE Compatibility : 1000BASE-SX

Datacom Compatibility: MS850

ITU Compatibility:

OTHER FEATURES

Form Factor	SFP
Interface	Optical Transceiver
Conformities	ETH
Fiber Type	Multimode
Fiber Quantity	Two
Connector Type	LC
Digital Diagnostics	Yes
LOS	Yes
Tunable	No
MultiRate	No
W.D.M.*	
W.D.M. Channel *	
Bi-directional complementary part number *	
Typical range (km)	0.55
Extended range * (km)	

** If applicable*

OPERATIONAL CONDITIONS

PARAMETER	MINIMUM	TYPICAL	MAXIMUM	UNIT
Operating Temperature	0		70	°C
Overload			0	dBm

OPTICAL TRANSMISSION PARAMETERS

PARAMETER	MINIMUM	TYPICAL	MAXIMUM	UNIT
Transmission power	-9.5		-4	dBm
Extinction Ratio	9			dB
Wavelength		850		nm
Spectral Width *			0.85	nm
Dispersion Tolerance *				ps/nm
Laser		VCSEL		

OPTICAL RECEPTION PARAMETERS

PARAMETER	MINIMUM	TYPICAL	MAXIMUM	UNIT
Wavelength		850		nm
Sensitivity			-17	dBm
Overload			0	dBm

EYE SAFETY

This is a Class1 Laser Product.

DATAKOM

Rua América, 1000 | 92990-000 | Eldorado do Sul | RS | Brasil

+55 51 3933 3000

www.datacom.com.br