



Part Number: 377.0161.00

Optical Transceiver SFP SS15 SDH ETH [S16.2/2.48G] [DD/DFB/A/OP:-5/RP:-20/30km]

PRODUCT DESCRIPTION

377.0161.00

Optical Transceiver SFP SS15 SDH ETH [S16.2/2.48G] [DD/DFB/A/OP:-5/RP:-20/30km]

FEATURES

SFP Optical Transceiver for 2.48G bps, with a typical range of 30 km.

Compatibilities:

IEEE Compatibility : NA

Datacom Compatibility: SS15

ITU Compatibility: S16.2

OTHER FEATURES

| | |
|--|---------------------|
| Form Factor | SFP |
| Interface | Optical Transceiver |
| Conformities | SDH ETH |
| Fiber Type | Singlemode |
| Fiber Quantity | Two |
| Connector Type | LC |
| Digital Diagnostics | Yes |
| LOS | Yes |
| Tunable | No |
| MultiRate | Yes |
| W.D.M.* | |
| W.D.M. Channel * | |
| Bi-directional complementary part number * | |
| Typical range (km) | 30 |
| Extended range * (km) | |

** If applicable*

OPERATIONAL CONDITIONS

| PARAMETER | MINIMUM | TYPICAL | MAXIMUM | UNIT |
|-----------------------|---------|---------|---------|------|
| Operating Temperature | 0 | | 70 | °C |
| Overload | | | 0 | dBm |

OPTICAL TRANSMISSION PARAMETERS

| PARAMETER | MINIMUM | TYPICAL | MAXIMUM | UNIT |
|------------------------|---------|---------|---------|-------|
| Transmission power | -5 | | 0 | dBm |
| Extinction Ratio | 8.2 | | | dB |
| Wavelength | | 1550 | | nm |
| Spectral Width * | | | 0.164 | nm |
| Dispersion Tolerance * | | | | ps/nm |
| Laser | | DFB | | |

OPTICAL RECEPTION PARAMETERS

| PARAMETER | MINIMUM | TYPICAL | MAXIMUM | UNIT |
|-------------|---------|---------|---------|------|
| Wavelength | | 1550 | | nm |
| Sensitivity | | | -20 | dBm |
| Overload | | | 0 | dBm |

EYE SAFETY

This is a Class1 Laser Product.

DATACOM

Rua América, 1000 | 92990-000 | Eldorado do Sul | RS | Brasil

+55 51 3933 3000

www.datacom.com.br