



Part Number: 377.0166.00

Optical Transceiver SFP MS13 ETH [-/1.25G] [-/FP/-/OP:-9/RP:-17/1km]

PRODUCT DESCRIPTION

377.0166.00

Optical Transceiver SFP MS13 ETH [-/1.25G] [-/FP/-/OP:-9/RP:-17/1km]

FEATURES

SFP Optical Transceiver for 1.25G bps, with a typical range of 1 km.

Compatibilities:

IEEE Compatibility : 1000BASE-LSX

Datacom Compatibility: MS13

ITU Compatibility:

OTHER FEATURES

Form Factor	SFP
Interface	Optical Transceiver
Conformities	ETH
Fiber Type	Multimode
Fiber Quantity	Two
Connector Type	LC
Digital Diagnostics	No
LOS	Yes
Tunable	No
MultiRate	No
W.D.M.*	
W.D.M. Channel *	
Bi-directional complementary part number *	
Typical range (km)	1
Extended range * (km)	

** If applicable*

OPERATIONAL CONDITIONS

PARAMETER	MINIMUM	TYPICAL	MAXIMUM	UNIT
Operating Temperature	0		70	°C
Overload			-1	dBm

OPTICAL TRANSMISSION PARAMETERS

PARAMETER	MINIMUM	TYPICAL	MAXIMUM	UNIT
Transmission power	-9		-3	dBm
Extinction Ratio	9			dB
Wavelength		1310		nm
Spectral Width *			4	nm
Dispersion Tolerance *				ps/nm
Laser		FP		

OPTICAL RECEPTION PARAMETERS

PARAMETER	MINIMUM	TYPICAL	MAXIMUM	UNIT
Wavelength		1310		nm
Sensitivity			-17	dBm
Overload			-1	dBm

EYE SAFETY

This is a Class1 Laser Product.

DATACOM

Rua América, 1000 | 92990-000 | Eldorado do Sul | RS | Brasil

+55 51 3933 3000

www.datacom.com.br