



Part Number: 377.0210.00

Optical Transceiver SFP ETH 1.25G 150km

PRODUCT DESCRIPTION

377.0210.00

Optical Transceiver SFP ETH 1.25G 150km

FEATURES

SFP Optical Transceiver for 1.25G bps, with a typical range of 150 km.

Compatibilities:

IEEE Compatibility : NA

Datacom Compatibility: DM-SFP-EZX-150I

ITU Compatibility:

RoHS Compatibility: Directive 2011/65/EU and 2015/863/EU

OTHER FEATURES

Form Factor	SFP
Interface	Optical Transceiver
Conformities	ETH
Fiber Type	Singlemode
Fiber Quantity	Two
Connector Type	LC/UPC
Digital Diagnostics	Yes
LOS	Yes
Tunable	No
MultiRate	No
W.D.M.*	
W.D.M. Channel *	
Bi-directional complementary part number *	
Typical range (km)	150
Extended range * (km)	
Forward Error Correction*	--

** If applicable*

OPERATIONAL CONDITIONS

PARAMETER	MINIMUM	TYPICAL	MAXIMUM	UNIT
Operating Temperature	-40		85	°C
Overload			-9	dBm

OPTICAL TRANSMISSION PARAMETERS

PARAMETER	MINIMUM	TYPICAL	MAXIMUM	UNIT
Transmission power	2.5		7	dBm
Extinction Ratio	9			dB
Wavelength		1550		nm
Spectral Width *			0.6	nm
Dispersion Tolerance *				ps/nm
Laser		DFB		

OPTICAL RECEPTION PARAMETERS

PARAMETER	MINIMUM	TYPICAL	MAXIMUM	UNIT
Wavelength		1550		nm
Sensitivity			-35	dBm
Overload			-9	dBm

EYE SAFETY

This is a Class1 Laser Product.

DATAKOM

Rua América, 1000 | 92990-000 | Eldorado do Sul | RS | Brasil

+55 51 3933 3000

www.datakom.com.br