



Part Number: 377.1207.01

Optical Transceiver XFP SS15 SDH ETH [-/10G] [DD/EML/A/OP:-1/RP:-15/40km]

PRODUCT DESCRIPTION

377.1207.01

Optical Transceiver XFP SS15 SDH ETH [-/10G] [DD/EML/A/OP:-1/RP:-15/40km]

FEATURES

XFP Optical Transceiver for 10G bps, with a typical range of 40 km.

Compatibilities:

IEEE Compatibility : 10GBASE-ER

Datacom Compatibility: SS15

ITU Compatibility: S-64.2

OTHER FEATURES

Form Factor	XFP
Interface	Optical Transceiver
Conformities	SDH ETH
Fiber Type	Singlemode
Fiber Quantity	Two
Connector Type	LC
Digital Diagnostics	Yes
LOS	Yes
Tunable	No
MultiRate	No
W.D.M.*	
W.D.M. Channel *	
Bi-directional complementary part number *	
Typical range (km)	40
Extended range * (km)	

* If applicable

OPERATIONAL CONDITIONS

PARAMETER	MINIMUM	TYPICAL	MAXIMUM	UNIT
Operating Temperature	0		70	°C
Overload			0	dBm

OPTICAL TRANSMISSION PARAMETERS

PARAMETER	MINIMUM	TYPICAL	MAXIMUM	UNIT
Transmission power	-1		2	dBm
Extinction Ratio	8.2			dB
Wavelength		1550		nm
Spectral Width *			0.164	nm
Dispersion Tolerance *				ps/nm
Laser		EML		

OPTICAL RECEPTION PARAMETERS

PARAMETER	MINIMUM	TYPICAL	MAXIMUM	UNIT
Wavelength		1550		nm
Sensitivity			-15	dBm
Overload			0	dBm

EYE SAFETY

This is a Class1 Laser Product.

DATACOM

Rua América, 1000 | 92990-000 | Eldorado do Sul | RS | Brasil

+55 51 3933 3000

www.datacom.com.br