



Part Number: 377.1414.00

Optical Transceiver QSFP28 ETH [-/100G] [DD/DFB/-/OP:-6,5/RP:-13/10km]100GBASE-4WDM-10

PRODUCT DESCRIPTION

377.1414.00

Optical Transceiver QSFP28 ETH [-/100G] [DD/DFB/-/OP:-6,5/RP:-13/10km]100GBASE-4WDM-10

FEATURES

QSFP28 Optical Transceiver for 100G bps, with a typical range of 10 km.

Compatibilities:

IEEE Compatibility : 100GBASE-4-10

Datacom Compatibility:

ITU Compatibility:

OTHER FEATURES

Form Factor	QSFP28
Interface	Optical Transceiver
Conformities	ETH
Fiber Type	Singlemode
Fiber Quantity	Two
Connector Type	LC
Digital Diagnostics	Yes
LOS	No
Tunable	No
MultiRate	No
W.D.M.*	
W.D.M. Channel *	
Bi-directional complementary part number *	
Typical range (km)	10
Extended range * (km)	

** If applicable*

OPERATIONAL CONDITIONS

PARAMETER	MINIMUM	TYPICAL	MAXIMUM	UNIT
Operating Temperature	0		70	°C
Overload			2.5	dBm

OPTICAL TRANSMISSION PARAMETERS

PARAMETER	MINIMUM	TYPICAL	MAXIMUM	UNIT
Transmission power	-6.5		2.5	dBm
Extinction Ratio	3.5			dB
Wavelength		1271 / 1291 / 1311 / 1331		nm
Spectral Width *				nm
Dispersion Tolerance *				ps/nm
Laser		DFB		

OPTICAL RECEPTION PARAMETERS

PARAMETER	MINIMUM	TYPICAL	MAXIMUM	UNIT
Wavelength		1271 / 1291 / 1311 / 1331		nm
Sensitivity			-13	dBm
Overload			2.5	dBm

EYE SAFETY

This is a Class1 Laser Product.

DATAKOM

Rua América, 1000 | 92990-000 | Eldorado do Sul | RS | Brasil
+55 51 3933 3000
www.datacom.com.br