



Part Number: 377.1418.10

Optical Transceiver QSFP28 ETH 100G 80km

PRODUCT DESCRIPTION

377.1418.10

Optical Transceiver QSFP28 ETH 100G 80km

FEATURES

QSFP28 Optical Transceiver for 100G bps, with a typical range of 80 km.

Compatibilities:

IEEE Compatibility : 100GBASE-ZR4

Datacom Compatibility: DM-QSFP28-ZR4-80

ITU Compatibility:

RoHS Compatibility: Directive 2011/65/EU and 2015/863/EU

OTHER FEATURES

Form Factor	QSFP28
Interface	Optical Transceiver
Conformities	ETH
Fiber Type	Singlemode
Fiber Quantity	Two
Connector Type	LC/UPC
Digital Diagnostics	Yes
LOS	No
Tunable	No
MultiRate	No
W.D.M.*	
W.D.M. Channel *	
Bi-directional complementary part number *	
Typical range (km)	80
Extended range * (km)	
Forward Error Correction*	It is mandatory to enable FEC CL91 on both sides of the host switches for proper operation of this optical transceiver model

** If applicable*

OPERATIONAL CONDITIONS

PARAMETER	MINIMUM	TYPICAL	MAXIMUM	UNIT
Operating Temperature	0		70	°C
Overload			-5	dBm

OPTICAL TRANSMISSION PARAMETERS

PARAMETER	MINIMUM	TYPICAL	MAXIMUM	UNIT
Transmission power	2		6.5	dBm
Extinction Ratio	6			dB
Wavelength		1295,1300,1304,1309		nm
Spectral Width *			1	nm
Dispersion Tolerance *				ps/nm
Laser		EML		

OPTICAL RECEPTION PARAMETERS

PARAMETER	MINIMUM	TYPICAL	MAXIMUM	UNIT
Wavelength		1295,1300,1304,1309		nm
Sensitivity			-27	dBm
Overload			-5	dBm

EYE SAFETY

This is a Class1 Laser Product.

DATACOM

Rua América, 1000 | 92990-000 | Eldorado do Sul | RS | Brasil

+55 51 3933 3000

www.datacom.com.br