



Part Number: 377.1424.00

Optical Transceiver SFP28 SLB1270 ETH [-/25G] [DD/DFB/-/OP:-1/RP:-19/40km] ER BIDI

PRODUCT DESCRIPTION

377.1424.00

Optical Transceiver SFP28 SLB1270 ETH [-/25G] [DD/DFB/-/OP:-1/RP:-19/40km] ER BIDI

FEATURES

SFP28 Optical Transceiver for 25G bps, with a typical range of 40 km.

Compatibilities:

IEEE Compatibility : 25GBASE-ER

Datacom Compatibility: SLB1270

ITU Compatibility:

OTHER FEATURES

Form Factor	SFP28
Interface	Optical Transceiver
Conformities	ETH
Fiber Type	Singlemode
Fiber Quantity	One
Connector Type	LC
Digital Diagnostics	Yes
LOS	No
Tunable	No
MultiRate	Yes
W.D.M.*	
W.D.M. Channel *	
Bi-directional complementary part number *	
Typical range (km)	40
Extended range * (km)	

** If applicable*

OPERATIONAL CONDITIONS

PARAMETER	MINIMUM	TYPICAL	MAXIMUM	UNIT
Operating Temperature	0		85	°C
Overload			-4	dBm

OPTICAL TRANSMISSION PARAMETERS

PARAMETER	MINIMUM	TYPICAL	MAXIMUM	UNIT
Transmission power	-1		6	dBm
Extinction Ratio	30			dB
Wavelength		1270		nm
Spectral Width *			1	nm
Dispersion Tolerance *				ps/nm
Laser		DFB		

OPTICAL RECEPTION PARAMETERS

PARAMETER	MINIMUM	TYPICAL	MAXIMUM	UNIT
Wavelength		1310		nm
Sensitivity			-19	dBm
Overload			-4	dBm

EYE SAFETY

This is a Class1 Laser Product.

DATACOM

Rua América, 1000 | 92990-000 | Eldorado do Sul | RS | Brasil

+55 51 3933 3000

www.datacom.com.br