



Part Number: 377.1500.00

Optical Transceiver QSFP-DD ETH 100G 120km

PRODUCT DESCRIPTION

377.1500.00

Optical Transceiver QSFP-DD ETH 100G 120km

FEATURES

QSFP-DD Optical Transceiver for 100G bps, with a typical range of 120 km.

Compatibilities:

IEEE Compatibility : 100ZR-OFEC-DP QPSK

Datacom Compatibility: DM-QDD100G-OZR

ITU Compatibility:

RoHS Compatibility: Directive 2011/65/EU and 2015/863/EU

OTHER FEATURES

Form Factor	QSFP-DD
Interface	Optical Transceiver
Conformities	ETH
Fiber Type	Singlemode
Fiber Quantity	Two
Connector Type	LC
Digital Diagnostics	Yes
LOS	Yes
Tunable	Yes
MultiRate	No
W.D.M.*	
W.D.M. Channel *	
Bi-directional complementary part number *	
Typical range (km)	120
Extended range * (km)	450
Forward Error Correction*	--

** If applicable*

OPERATIONAL CONDITIONS

PARAMETER	MINIMUM	TYPICAL	MAXIMUM	UNIT
Operating Temperature	0		70	°C
Overload			0	dBm

OPTICAL TRANSMISSION PARAMETERS

PARAMETER	MINIMUM	TYPICAL	MAXIMUM	UNIT
Transmission power	-6		0	dBm
Extinction Ratio				dB
Wavelength		Tunable C-Band (50 & 100Ghz tunnable)		nm
Spectral Width *				nm
Dispersion Tolerance *	8600			ps/nm
Laser		Coherent		
TX OSNR	34			dB

OPTICAL RECEPTION PARAMETERS

PARAMETER	MINIMUM	TYPICAL	MAXIMUM	UNIT
Wavelength		Tunable C-Band (50 & 100Ghz tunnable)		nm
Sensitivity			-32	dBm
Low OSNR	-25		0	dBm
RX OSNR			16.5	dB
Overload			0	dBm

EYE SAFETY

This is a Class1 Laser Product.

DATACOM

Rua América, 1000 | 92990-000 | Eldorado do Sul | RS | Brasil

+55 51 3933 3000

www.datacom.com.br