



Part Number: 377.1517.00

Optical Transceiver QSFP-DD ETH 400G 2km

PRODUCT DESCRIPTION

377.1517.00

Optical Transceiver QSFP-DD ETH 400G 2km

FEATURES

QSFP-DD Optical Transceiver for 400G bps, with a typical range of 2 km.

Compatibilities:

IEEE Compatibility : 400GBASE-DR4

Datacom Compatibility: DM-QDD400G-EDR4-2

ITU Compatibility:

RoHS Compatibility: Directive 2011/65/EU and 2015/863/EU

OTHER FEATURES

Form Factor	QSFP-DD
Interface	Optical Transceiver
Conformities	ETH
Fiber Type	Singlemode
Fiber Quantity	MPO
Connector Type	MPO-12 APC(SM)
Digital Diagnostics	Yes
LOS	No
Tunable	No
MultiRate	No
W.D.M.*	
W.D.M. Channel *	
Bi-directional complementary part number *	
Typical range (km)	2
Extended range * (km)	
Forward Error Correction*	--

** If applicable*

OPERATIONAL CONDITIONS

PARAMETER	MINIMUM	TYPICAL	MAXIMUM	UNIT
Operating Temperature	0		70	°C
Overload			4	dBm

OPTICAL TRANSMISSION PARAMETERS

PARAMETER	MINIMUM	TYPICAL	MAXIMUM	UNIT
Transmission power	-2.9		4	dBm
Extinction Ratio	3.5			dB
Wavelength		1311		nm
Spectral Width *				nm
Dispersion Tolerance *				ps/nm
Laser				

OPTICAL RECEPTION PARAMETERS

PARAMETER	MINIMUM	TYPICAL	MAXIMUM	UNIT
Wavelength		1311		nm
Sensitivity			-4.4	dBm
Overload			4	dBm

EYE SAFETY

This is a Class1 Laser Product.

DATACOM

Rua América, 1000 | 92990-000 | Eldorado do Sul | RS | Brasil

+55 51 3933 3000

www.datacom.com.br